



## Product Line Overview

The FastSet product line combines speed with toughness to provide our customers with a product to speed up their production without sacrificing the properties that they desire. With ratios that are meter mix friendly and gel times ranging from 35 seconds up to 3 minutes this line of products can pump up your part production.

## Product Line Highlights

- Fast setting polyurethane with exceptional green strength
- Semi rigid feel with great impact strength
- A 1:1 mix ratio by volume, great for meter mix or cartridge gun applications

## Popular Products from our FastSet Line

Product Name	Gel Time (minutes)	Shore Hardness	Tensile Strength	Elongation	Impact Strength	Flex Modulus	HDT
FSD185HT	60 seconds	85D +/-5	6500	8%	1.6 ft/lbs	180000	252F
FSD385HT	180 seconds	85D +/-5	6500	8%	1.6 ft/lbs	180000	205F
FSD185UV	50 seconds	80D +/-5	9000	6%	1.8 ft/lbs	425000	235F
FSD180FR	50 seconds	80D +/-5	5000	2%	1.4 ft/lbs	180000	203F
FSD3585HT	35 seconds	85D +/-5	6500	8%	1.6 ft/lbs	180000	255F

HT = High Heat Deflection Temperature  
UV = Additional UV stability  
FR = Additional Flame Retardant